

**Description**

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1580A3T4DX                             |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-484-1292                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1580A3T4DX Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.363 Inches Nominal                                       |
| <b>Fastener Length:</b>                               | 0.598 Inches Minimum And 0.613 Inches Maximum              |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.339 Inches Minimum And 0.381 Inches Maximum              |
| <b>Grip Diameter:</b>                                 | 0.2041 Inches Minimum And 0.2051 Inches Maximum            |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                              |
| <b>End Item Identification:</b>                       | F-16/b/c/d   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.240 Inches Minimum And 0.260 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum                                       |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                                     |
| <b>Surface Treatment Document And Classification:</b> | Qq-o-35 Fed Spec Single Treatment Response Overall         |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1580 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3T4DX> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.