



Military-Fasteners.com

P/N NAS1580A3T4DX

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A3T4DX
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-484-1292
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1580A3T4DX Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.363 Inches Nominal
<b>Fastener Length:</b>	0.598 Inches Minimum And 0.613 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.339 Inches Minimum And 0.381 Inches Maximum
<b>Grip Diameter:</b>	0.2041 Inches Minimum And 0.2051 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>End Item Identification:</b>	F-16/b/c/d
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment Document And Classification:</b>	Qq-o-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1580 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3T4DX> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.