

# P/N NAS1580A3T6D

Military-Fasteners.com

#### Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

#### Order this part online

#### **Additional Information**

SKU / Model:	NAS1580A3T6D
Minimum Qty (MOQ):	10
NSN:	5305-01-204-4203
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1580A3T6D Specifications

За
Right-hand
0.338 Inches Minimum And 0.388 Inches Maximum
0.723 Inches Minimum And 0.753 Inches Maximum
Flat Countersunk
0.339 Inches Minimum And 0.381 Inches Maximum
0.1890 Inches Minimum And 0.1895 Inches Maximum
0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Offset Cruciform (torque Set)
0.190 Inches
0.365 Inches Minimum And 0.385 Inches Maximum
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
0.597 Inches Minimum First Hole And 0.647 Inches Maximum First Hole
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s- 6049 Mil Spec 3rd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1580 Professional/industrial Association Standard

### How to Order

Order this close tolerance screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS1580A3T6D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.