

P/N NAS1580A4R14

Description

Fastener Length: 1-9/32", Thread: 1/4-28, Thread Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1580A4R14


Minimum Qty (MOQ): 20

NSN: 5305-01-168-9232

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1580A4R14 Specifications

| Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.403 Inches Maximum Fastener Length: 1.263 Inches Minimum And 1.293 Inches Maximum | |
|---|---------------------------------------|
| Thread Length: 0.403 Inches Maximum Fastener Length: 1.263 Inches Minimum And 1.293 Inches Maximum | |
| Fastener Length: 1.263 Inches Minimum And 1.293 Inches Maximum | |
| | |
| | |
| Head Style: Flat Countersunk | |
| Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum | |
| Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum | |
| Internal Drive Style: Torque-set Ribbed | |
| Nominal Thread Diameter: 0.250 Inches | |
| Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum | |
| Thread Quantity Per Inch: 28 | |
| Minimum Tensile Strength: 160000 Pounds Per Square Inch | |
| Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall | |
| Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum | |
| Surface Finish: 32.0 Microinches Grip | |
| Surface Finish: 32.0 Microinches Threads | |
| Material: Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8735 Overall | |
| Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall | sponse Overall Or Mil-s-6049 Mil Spec |
| Surface Treatment: Cadmium Overall And Chromate Overall | |
| Surface Treatment Document And Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall | |
| Thread Series Designator: Unjf | |
| Specification/standard Data: 80205-nas1580 Professional/industrial Association Standard | |

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1580A4R14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.