

P/N NAS1580A4R28D

Description

Fastener Length: 2-5/32", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1580A4R28D

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-522-0921

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1580A4R28D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.393 Inches Minimum And 0.413 Inches Maximum
Fastener Length:	2.138 Inches Minimum And 2.168 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.464 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	C-17a Acft
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw Close Tolerance
Material:	Steel Comp 4140 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4R28D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.