

Description

Fastener Length: 2-5/32", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1580A4R28D
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-522-0921
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1580A4R28D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.393 Inches Minimum And 0.413 Inches Maximum
Fastener Length:	2.138 Inches Minimum And 2.168 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.464 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	C-17a Acft
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw Close Tolerance
Material:	Steel Comp 4140 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4R28D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.