

Description

Fastener Length: 3/8", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A4R34D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-468-2932
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1580A4R34D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.403 Inches Nominal
Fastener Length:	0.403 Inches Nominal
Head Style:	Flush
Head Diameter:	0.50663 Inches Nominal
Head Height:	0.1110 Inches Nominal
Grip Diameter:	0.249 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.187 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	5790 Pounds Per Square Inch
Thread Pitch In Millimeters:	0.9
External Thread Tolerance Class:	3a
Material:	Steel Comp 4130 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Passivate Overall Or Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Overall Or Qq-p-416,typeii,class2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4R34D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.