

**Description**

Fastener Length: 3/8", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1580A4R34D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-468-2932
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1580A4R34D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.403 Inches Nominal
<b>Fastener Length:</b>	0.403 Inches Nominal
<b>Head Style:</b>	Flush
<b>Head Diameter:</b>	0.50663 Inches Nominal
<b>Head Height:</b>	0.1110 Inches Nominal
<b>Grip Diameter:</b>	0.249 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.187 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	5790 Pounds Per Square Inch
<b>Thread Pitch In Millimeters:</b>	0.9
<b>External Thread Tolerance Class:</b>	3a
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall Or Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Overall Or Qq-p-416,typeii,class2 Fed Spec 1st Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4R34D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.