



Military-Fasteners.com

P/N NAS1580A4T14Y

Description

Fastener Length: 1-9/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1580A4T14Y |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-431-0925 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1580A4T14Y Specifications

| | |
|---------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.378 Inches Minimum And 0.428 Inches Maximum |
| Fastener Length: | 1.263 Inches Minimum And 1.293 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.464 Inches Minimum And 0.507 Inches Maximum |
| Grip Diameter: | 0.248 Inches Minimum And 0.249 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 4140 Overall And Steel Comp 4340 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T14Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.