

## P/N NAS1580A4T25

## **Description**

Fastener Length: 1-31/32", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS1580A4T25

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-063-5062

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1580A4T25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.373 Inches Minimum And 0.423 Inches Maximum
Fastener Length:	1.950 Inches Minimum And 1.980 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.464 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.557 Inches Minimum And 1.577 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T25</a> and selecting the quantity you want then click "add to cart".