

Description

Fastener Length: 29/32", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A4T8X
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-308-9975
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1580A4T8X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.403 Inches Nominal
Fastener Length:	0.888 Inches Minimum And 0.918 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.5066 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2490 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty li,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A4T8X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.