

Description

Fastener Length: 1-51/64", Thread: 5/16-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A5R23
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-501-5664
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1580A5R23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Nominal
Fastener Length:	1.799 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.578 Inches Minimum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.438 Inches Nominal
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A5R23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.