

P/N NAS1580A6T11

Description

Fastener Length: 1-19/64", Thread: 3/8-24, Thread Length: 39/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1580A6T11

Minimum Qty (MOQ):

NSN: 5305-01-206-0102

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS1580A6T11 Specifications

Thread Direction: Right-hand Thread Length: 0.569 Inches Minimum And 0.619 Inches Maximum Fastener Length: 1.267 Inches Minimum And 1.297 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.710 Inches Minimum And 0.7604 Inches Maximum Head Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.375 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Internal Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 10.10 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp B740 Overall Miles-5626 Mil Spec 1st Material Response Overall Or Miles-5000 Mil Spec 2nd Material Response Overall Or Miles-6049 Mil Spec 3rd Material Response Overall Classification: Unif		
Thread Length: 0.569 Inches Minimum And 0.619 Inches Maximum Fastener Length: 1.267 Inches Minimum And 1.297 Inches Maximum Head Style: Flat Countersunk Head Style: 0.7170 Inches Minimum And 0.7604 Inches Maximum Grip Diameter: 0.7170 Inches Minimum And 0.7604 Inches Maximum Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Internal Drive Style: 0ffset Cruciform (torque Set) Nominal Thread Diameter: 0.375 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec Surface Treatment Document And Classification: Q-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Chassification: Unif	Thread Class:	3a
Fastener Length: 1.267 Inches Minimum And 1.297 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.7170 Inches Minimum And 0.7604 Inches Maximum Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.375 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 10.1.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Chadium Overall And Chromate Overall	Thread Direction:	Right-hand
Head Diameter: 0.7170 Inches Minimum And 0.7604 Inches Maximum Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Internal Drive Style: 0ffset Cruciform (torque Set) Nominal Thread Diameter: 0.375 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Countersink Angle: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec Surface Treatment: Cadmium Overall And Chromate Overall Classification: Unjf	Thread Length:	0.569 Inches Minimum And 0.619 Inches Maximum
Head Diameter: 0.7170 Inches Minimum And 0.7604 Inches Maximum Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Internal Drive Style: 0ffset Cruciform (torque Set) Nominal Thread Diameter: 0.375 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Wil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec Surface Treatment: 0q-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Classification: Thread Series Designator: Unif	Fastener Length:	1.267 Inches Minimum And 1.297 Inches Maximum
Sirjo Diameter: 10.3735 Inches Minimum And 0.3745 Inches Maximum 10.3745 Inches Minimum And 0.3745 Inches Maximum 10.375 Inches 10.375 Inches Maximum 10.375 Inches Maximum 10.375 Inches 10.375 Inches Maximum 10.3	Head Style:	Flat Countersunk
Offset Cruciform (torque Set) Nominal Thread Diameter: O.375 Inches Grip Length: O.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: Hardness Rating: O.600 Pounds Per Square Inch Hardnes	Head Diameter:	0.7170 Inches Minimum And 0.7604 Inches Maximum
Nominal Thread Diameter: 0.375 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec Surface Treatment Document And Classification: Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum 160000 Pounds Per Square Inch 1	Internal Drive Style:	Offset Cruciform (torque Set)
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Classification: Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Chread Series Designator: Unjf	Nominal Thread Diameter:	0.375 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Thread Quantity Per Inch:	24
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Chread Series Designator: Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Unjf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Re	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Over	Surface Finish:	32.0 Microinches Threads
Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Classification: Classification: Classification: Oq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Unjf	Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Unjf	Material Document And Classification:	
Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1580 Professional/industrial Association Standard	Thread Series Designator:	Unjf
50203 Na31300 Professional, industrial Patalla	Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A6T11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.