

Description

Fastener Length: 1-39/64", Thread: 3/8-24, Thread Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A6T16
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-438-8275



\* See page 2 for technical characteristics

## P/N NAS1580A6T16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.569 Inches Minimum And 0.619 Inches Maximum
<b>Fastener Length:</b>	1.579 Inches Minimum And 1.609 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.760 Inches Nominal
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A6T16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.