



Military-Fasteners.com

P/N NAS1580C3R12P

Description

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 23/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C3R12P
Minimum Qty (MOQ):	10
NSN:	5305-01-556-9597
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1580C3R12P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	1.113 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum
Grip Diameter:	0.189 Inches Minimum
Internal Drive Style:	Torque-set Ribbed
End Item Identification:	C-17a Aircraft
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.750 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty li. Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C3R12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.