

# **P/N NAS1580C3T11P**

### **Description**

Fastener Length: 1-1/16", Thread: 10-32, Thread Length: 23/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1580C3T11P
Minimum Qty (MOQ):	10
NSN:	5305-01-471-0571
Schedule B:	7318.15.8085
FCCN:	FAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1580C3T11P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	1.036 Inches Minimum And 1.066 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty Ii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this close tolerance screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C3T11P">https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C3T11P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.