



Military-Fasteners.com

P/N NAS1580C3T14D

Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 23/64", NAS1580 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C3T14D
Minimum Qty (MOQ):	1
NSN:	5305-01-421-4226
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS1580C3T14D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	1.223 Inches Minimum And 1.253 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.112 Inches Minimum First Hole And 1.132 Inches Maximum First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5765599999999999jgaams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C3T14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.