

P/N NAS1580C3T16D

Description

Fastener Length: 1-3/8", Thread: 10-32, Thread Length: 23/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1580C3T16D

Minimum Qty (MOQ):

NSN: 5305-01-421-4227

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



^{*} See page 2 for technical characteristics

P/N NAS1580C3T16D Specifications

3a
Right-hand
0.363 Inches Nominal
1.348 Inches Minimum And 1.378 Inches Maximum
Flat Countersunk
0.339 Inches Minimum And 0.381 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Offset Cruciform (torque Set)
0.190 Inches
0.990 Inches Minimum And 1.010 Inches Maximum
32
160000 Pounds Per Square Inch
99.0 Degrees Minimum And 101.0 Degrees Maximum
1.237 Inches Minimum First Hole And 1.257 Inches Maximum First Hole
Iron Alloy 660 Overall
Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Passivate Overall
Qq-p-35 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C3T16D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.