

P/N NAS1580C4H5

Description

Fastener Length: 23/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1580C4H5

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-170-6195

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1580C4H5 Specifications

Thread Direction: Right-hand Thread Length: 0.378 Inches Minimum And 0.428 Inches Maximum Fastener Length: 0.700 Inches Minimum And 0.730 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.507 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.526 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment Document And Classification: Q-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf		
Thread Length: Fastener Length: 0.700 Inches Minimum And 0.428 Inches Maximum Flat Countersunk 0.464 Inches Minimum And 0.507 Inches Maximum Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2495 Inches Minimum And 0.507 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Internal Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Iron Alloy 660 Overall Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Chapter of the Special Special Preatment Response Overall Oq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Class:	3a
Fastener Length: 0.700 Inches Minimum And 0.730 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Ansstraid Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unif	Thread Direction:	Right-hand
Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Countersink Angle: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: 4ms5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Length:	0.378 Inches Minimum And 0.428 Inches Maximum
Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum O.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unjf	Fastener Length:	0.700 Inches Minimum And 0.730 Inches Maximum
Grip Diameter: Internal Drive Style: High-torque Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unjf	Head Style:	Flat Countersunk
Internal Drive Style:High-torqueNominal Thread Diameter:0.250 InchesGrip Length:0.302 Inches Minimum And 0.322 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Head Diameter:	0.464 Inches Minimum And 0.507 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.302 Inches Minimum And 0.322 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length:0.302 Inches Minimum And 0.322 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Internal Drive Style:	High-torque
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Iron Alloy 660 Overall Material Document And Classification: Surface Treatment: Passivate Overall Oq-p-35 Fed Spec Single Treatment Response Overall Qq-p-35 Fed Spec Single Treatment Response Overall Unjf	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 10000 Pounds Per Square Inch 32.0 Microinches Grip Surface Finish: 10000 Pounds Per Square Inch 32.0 Microinches Grip 32.0 Microinches Threads Material: 100 Alloy 660 Overall Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn St	Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Quantity Per Inch:	28
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Sin	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Material: Iron Alloy 660 Overall Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ms5732 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Classification: Thread Series Designator: Unjf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Classification: Thread Series Designator: Iron Alloy 660 Overall Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ms5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ms5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Classification: Thread Series Designator: Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Respons	Surface Finish:	32.0 Microinches Threads
Single Material Document And Classification: Single Material Response Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Classification: Thread Series Designator: Unjf	Material:	Iron Alloy 660 Overall
Surface Treatment Document And Classification: Thread Series Designator: Unjf	Material Document And Classification:	· · · · · · · · · · · · · · · · · · ·
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Unjf Unjf	Surface Treatment:	Passivate Overall
	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1580 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4H5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4H5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4H5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4H5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4H5 and selecting the your cart yo