

Description

Fastener Length: 1-9/32", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1580C4T14D    |
| Minimum Qty (MOQ): | 1 EA             |
| NSN:               | 5305-01-421-9543 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | 9A991            |



\* See page 2 for technical characteristics

## P/N NAS1580C4T14D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.403 Inches Nominal  |
| <b>Fastener Length:</b>   | 1.263 Inches Minimum And 1.293 Inches Maximum                 |
| <b>Head Style:</b>  | Flat Countersunk  |
| <b>Head Diameter:</b>   | 0.111 Inches Nominal  |
| <b>Grip Diameter:</b>   | 0.2485 Inches Minimum And 0.2495 Inches Maximum               |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum Threads And 0.086 Inches Maximum Threads |
| <b>Internal Drive Style:</b>  | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches  |
| <b>Grip Length:</b>   | 0.865 Inches Minimum And 0.885 Inches Maximum                 |
| <b>Thread Quantity Per Inch:</b>  | 28  |
| <b>Minimum Tensile Strength:</b>  | 180000 Pounds Per Square Inch                                 |
| <b>Countersink Angle:</b>   | 99.0 Degrees Minimum And 101.0 Degrees Maximum                |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.137 Inches Minimum Threads And 1.187 Inches Maximum Threads |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-35 Fed Spec Single Treatment Response Overall            |
| <b>Thread Series Designator:</b>  | Unjf  |
| <b>Specification/standard Data:</b>                                     | 80205-nas1580 Professional/industrial Association Standard    |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.