

Description

Fastener Length: 1-9/32", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1580C4T14D |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-421-9543 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N NAS1580C4T14D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.403 Inches Nominal |
| Fastener Length: | 1.263 Inches Minimum And 1.293 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.111 Inches Nominal |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum Threads And 0.086 Inches Maximum Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.137 Inches Minimum Threads And 1.187 Inches Maximum Threads |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1580 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.