

Description

length: 0.590", thread: 1/4-28 shear, flush head, corrosion resistant steel, offset cruciform

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C4T3
Minimum Qty (MOQ):	10
NSN:	5305-01-494-7020
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1580C4T3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.403 Inches Nominal
Fastener Length:	0.575 Inches Minimum And 0.605 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.464 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Torque-set Ribbed
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	5790 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5853 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C4T3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.