

P/N NAS1580C4T4P

Description

Fastener Length: 21/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1580C4T4P

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-258-6041

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1580C4T4P Specifications

Thread Direction: Right-hand Thread Length: 0.378 Inches Minimum And 0.428 Inches Maximum Fastener Length: 0.638 Inches Minimum And 0.668 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn		
Thread Length: 0.378 Inches Minimum And 0.428 Inches Maximum Fastener Length: 0.638 Inches Minimum And 0.668 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Class:	3a
Fastener Length: Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum And 101.0 Degrees Maximum Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Internal Drive Ribbed Material: Material Document And Classification: Material Document And Classification: Ans 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Direction:	Right-hand
Head Style: Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Material Document And Classification: Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Length:	0.378 Inches Minimum And 0.428 Inches Maximum
Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material Pocument And Classification: Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Fastener Length:	0.638 Inches Minimum And 0.668 Inches Maximum
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Head Style:	Flat Countersunk
Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Head Diameter:	0.464 Inches Minimum And 0.507 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.240 Inches Minimum And 0.260 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length: Countity Per Inch: Binimum Tensile Strength: 160000 Pounds Per Square Inch 1	Internal Drive Style:	Offset Cruciform (torque Set)
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Quantity Per Inch:	28
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish: Special Features: Internal Drive Ribbed Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Special Features: Material: Internal Drive Ribbed Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Surface Finish:	32.0 Microinches Grip
Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Special Features:	Internal Drive Ribbed
Material Document And Classification:	Material:	Iron Alloy 660 Overall
Sta Single Material Nesponse Overall	Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Og-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf	Thread Series Designator:	Unjf
Specification/standard Data: 80205-nas1580 Professional/industrial Association Standard	Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T4P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T4P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T4P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T4P and selecting the quantity you want of the property of the p