

P/N NAS1580C4T7

Description

Fastener Length: 27/32", Thread: 1/4-28, Thread Length: 27/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C4T7
Minimum Qty (MOQ):	10
NSN:	5305-01-057-9335
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1580C4T7 Specifications

Thread Direction: Right-hand Thread Length: 0.387 Inches Minimum And 0.428 Inches Maximum Fastener Length: 0.826 Inches Minimum And 0.856 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.4285 Inches Minimum And 0.507 Inches Maximum Internal Drive Style: 0.458 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: 0.500 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Internal Drive Style: 0.428 Inches Minimum And 0.448 Inches Maximum Internal Drive Style: 0.428 Inches Minimum And 0.448 Inches Maximum Internal Drive Style: 0.428 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.428 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal Diameter: 0.408 Inches Minimum And 0.448 Inches Maximum Internal		
Thread Length: 0.387 Inches Minimum And 0.428 Inches Maximum 0.826 Inches Minimum And 0.856 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 10.10 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Class:	3a
Fastener Length: Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Direction:	Right-hand
Head Style: Flat Countersunk Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Length:	0.387 Inches Minimum And 0.428 Inches Maximum
Head Diameter: 0.464 Inches Minimum And 0.507 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Fastener Length:	0.826 Inches Minimum And 0.856 Inches Maximum
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Head Style:	Flat Countersunk
Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Head Diameter:	0.464 Inches Minimum And 0.507 Inches Maximum
Nominal Thread Diameter: 0.250 Inches 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length: O.428 Inches Minimum And O.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Internal Drive Style:	Offset Cruciform (torque Set)
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Thread Quantity Per Inch:	28
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Surface Finish: Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material: Iron Alloy 660 Overall Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Surface Finish:	32.0 Microinches Grip
Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:	Material:	Iron Alloy 660 Overall
Std Single Material Response Overall	Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment: Passivate Overall	Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall		Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf	Thread Series Designator:	Unjf
Specification/standard Data: 80205-nas1580 Professional/industrial Association Standard	Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C4T7 and selecting the