

Description

Fastener Length: 1-9/64", Thread: 1/4-24, Thread Length: 33/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C5T10
Minimum Qty (MOQ):	5
NSN:	5305-01-276-5820
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1580C5T10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.476 Inches Minimum And 0.526 Inches Maximum
Fastener Length:	1.111 Inches Minimum And 1.141 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.578 Inches Minimum And 0.634 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1580C5T10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.