



Military-Fasteners.com

P/N NAS1580C5T9Y

Description

Fastener Length: 1-5/64", Thread: 5/16-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C5T9Y
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-399-3794
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1580C5T9Y Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Nominal
Fastener Length:	1.048 Inches Minimum And 1.078 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.6335 Inches Maximum
Grip Diameter:	0.3427 Inches Minimum And 0.3432 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C5T9Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.