



Military-Fasteners.com

P/N NAS1580C6T40D

Description

Fastener Length: 3-3/32", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580C6T40D
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-590-6398
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1580C6T40D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Nominal
Fastener Length:	3.094 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.760 Inches Nominal
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.500 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Item Has Drilled Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580C6T40D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.