

**Description**

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 3/8", NAS1580 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                  |
|-------------------------|----------------------------------|
| SKU / Model:            | NAS1580V3R14                     |
| Minimum Qty (MOQ):      | 5                                |
| NSN:                    | 5305-01-217-2186                 |
| Schedule B:             | 8108.90.3060                     |
| ECCN:                   | EAR99                            |
| National Motor Freight: | 096660, Screws Noi Silver Plated |



\* See page 2 for technical characteristics

## P/N NAS1580V3R14 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.338 Inches Minimum And 0.388 Inches Maximum  |
| <b>Fastener Length:</b>                      | 1.223 Inches Minimum And 1.253 Inches Maximum  |
| <b>Head Style:</b>                           | Flat Countersunk   |
| <b>Head Diameter:</b>                        | 0.339 Inches Minimum And 0.381 Inches Maximum  |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Internal Drive Style:</b>                 | Offset Cruciform (torque Set)  |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 0.865 Inches Minimum And 0.885 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                    | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads   |
| <b>Special Features:</b>                     | Internal Drive Ribbed  |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall  |
| <b>Material Document And Classification:</b> | Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas1580 Professional/industrial Association Standard                                       |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.