

Description

Fastener Length: 1-11/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1580V3T7D |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-467-6664 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1580V3T7D Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.3630 Inches Nominal |
| Fastener Length: | 1.149 Inches Minimum And 1.179 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.3813 Inches Nominal |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| End Item Identification: | C-17a Aircraft |
| Nominal Thread Diameter: | 0.1900 Inches |
| Grip Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 3180 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Special Features: | Point Of Screw Shall Be Flat And Chamfered; Heat Treat 160-180 Ksi FtU Per Ams 4928 Or Ams 4967; The Offset Cruciform Recess Diameter Is 0.248 Inch |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Ams4928 Assn Std 1st Material Response Overall Or Ams4967 Assn Std 2nd Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V3T7D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.