

Description

Fastener Length: 27/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580V4R7
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-167-7634
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1580V4R7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.378 Inches Minimum And 0.428 Inches Maximum
Fastener Length:	0.826 Inches Minimum And 0.856 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.464 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Internal Drive Ribbed
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V4R7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.