

Description

Fastener Length: 1-17/64", Thread: 5/16-24, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580V5T12
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-183-8733
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N NAS1580V5T12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.476 Inches Minimum And 0.526 Inches Maximum
Fastener Length:	1.236 Inches Minimum And 1.266 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.5780 Inches Minimum And 0.6335 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Internal Drive Ribbed
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V5T12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.