

Description

Fastener Length: 1-5/8", Thread: 5/16-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580V5T18
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-567-7945
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	061080, Bus Bar System Noi



* See page 2 for technical characteristics

P/N NAS1580V5T18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Nominal
Fastener Length:	1.626 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.578 Inches Minimum And 0.633 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.125 Inches Nominal
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Flush Rivet Head Between
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V5T18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.