

Description

Fastener Length: 1-19/64", Thread: 3/8-24, Thread Length: 39/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580V6T11
Minimum Qty (MOQ):	1
NSN:	5305-01-538-0943
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



P/N NAS1580V6T11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.569 Inches Minimum And 0.619 Inches Maximum
Fastener Length:	1.267 Inches Minimum And 1.297 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.717 Inches Minimum And 0.760 Inches Maximum
Grip Diameter:	0.374 Inches Nominal
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V6T11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.