

Description

Fastener Length: 1-7/8", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580V6T21
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-537-9699
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093483, Bolts,nuts Or Screws,noi Iron Or

NO IMAGE
AVAILABLE

P/N NAS1580V6T21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Nominal
Fastener Length:	1.906 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.717 Inches Nominal
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	B1-b Acft Nsn 6515-01-537-9710
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.312 Inches Nominal
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, Flush Head
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 National Std/spec Single Material Response Overall Or Ams4967 National Std/spec Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V6T21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.