

**Description**

Fastener Length: 2-1/8", Thread: 3/8-24, Thread Length: 19/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1580V6T25
Minimum Qty (MOQ):	1
NSN:	5305-01-537-9711
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NAS1580V6T25



## P/N NAS1580V6T25 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.594 Inches Nominal
<b>Fastener Length:</b>	2.156 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.717 Inches Nominal
<b>Grip Diameter:</b>	0.373 Inches Minimum And 0.374 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>End Item Identification:</b>	B1-b Acft
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.562 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Flush Head
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4928 National Std/spec Single Material Response Overall Or Ams4967 National Std/spec Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V6T25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.