

Description

Fastener Length: 2-1/8", Thread: 3/8-24, Thread Length: 19/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1580V6T25 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-537-9711 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NAS1580V6T25



P/N NAS1580V6T25 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Nominal |
| Fastener Length: | 2.156 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.717 Inches Nominal |
| Grip Diameter: | 0.373 Inches Minimum And 0.374 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| End Item Identification: | B1-b Acft |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.562 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Bolt, Flush Head |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4928 National Std/spec Single Material Response Overall Or Ams4967 National Std/spec Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580V6T25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.