

P/N NAS1581A4H6

Military-Fasteners.com

Description

Fastener Length: 25/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1581A4H6
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-465-5486
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1581A4H6 Specifications

Thread Class: 3a Thread Direction: Right-hand Phread Length: 0.378 Inches Minimum And 0.428 Inches Maximum *astener Length: 0.378 Inches Minimum And 0.793 Inches Maximum *ead Style: Flat Countersunk *ead Diameter: 0.350 Inches Minimum And 0.399 Inches Maximum *fead Diameter: 0.350 Inches Minimum And 0.399 Inches Maximum *fead Diameter: 0.3260 Inches Minimum And 0.2495 Inches Maximum *fere Style: High-torque Nominal Thread Diameter: 0.250 Inches 0.250 Inches Stinimum And 0.385 Inches Maximum 0.365 Inches Minimum And 0.385 Inches Maximum Strip Length: 0.365 Inches Minimum And 0.385 Inches Maximum Thread Quantity Per Inch: 28 Yandama Engles Strength: 160000 Pounds Per Square Inch Aradness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Starface Finish: 32.0 Microinches Grip Starface Finish: 32.0 Microinches Threads Starface Finish: 32.0 Microinches Threads
Fastener Length:0.763 Inches Minimum And 0.793 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.350 Inches Minimum And 0.399 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.250 Inches Minimum And 0.385 Inches MaximumThread Quantity Per Inch:0.365 Inches Minimum And 0.385 Inches MaximumChread Quantity Per Inch:60000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches Threads
Head Style:Flat CountersunkHead Diameter:0.350 Inches Minimum And 0.399 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches Maximumnternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.250 InchesMinimum And 0.385 Inches MaximumStrip Length:0.365 Inches Minimum And 0.385 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 10.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Head Diameter:0.350 Inches Minimum And 0.399 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueVominal Thread Diameter:0.250 Inches0.365 Inches Minimum And 0.385 Inches MaximumStrip Length:0.365 Inches Minimum And 0.385 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches Maximumnternal Drive Style:High-torqueWominal Thread Diameter:0.250 Inches0.365 Inches Minimum And 0.385 Inches MaximumGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square Inch160000 Pounds Per Square Inch36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Internal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.250 Inches0.365 Inches Minimum And 0.385 Inches MaximumGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Nominal Thread Diameter:0.250 InchesGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumChread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square Inch160000 Pounds Per Square Inch36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHardness Rating:36.0 Rockwell C Minimum And 101.0 Degrees MaximumCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Grip Length:0.365 Inches Minimum And 0.385 Inches MaximumGrip Length:0.365 Inches Minimum And 0.385 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchIardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSteel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
Overall
Material Document AndMil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rdClassification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator: Unjf
Specification/standard Data: 80205-nas1581 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581A4H6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.