

Description

length: 0.487", thread: 10-32, shear, flush reduced head, cadmium plated corrosion resistant steel, offset cruciform, NAS1581 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1581C3T2P |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-500-6186 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1581C3T2P Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.363 Inches Nominal |
| Fastener Length: | 0.488 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.305 Inches Nominal |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| End Item Identification: | C0104,aircraft, Harrier Av-8b |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.125 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Asm 5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1581C3T2P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.