

**Description**

length: 0.549", thread: 10-32, shear, flush reduced head, cadmium plated corrosion resistant steel, offset cruciform

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1581C3T3P
Minimum Qty (MOQ):	25
NSN:	5305-01-417-2882
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1581C3T3P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.377 Inches Minimum And 0.387 Inches Maximum
<b>Fastener Length:</b>	0.534 Inches Minimum And 0.564 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.258 Inches Minimum And 0.305 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>End Item Identification:</b>	F-16
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.177 Inches Minimum And 0.197 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1581C3T3P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.