

Description

Fastener Length: 1-5/32", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581C4T12
Minimum Qty (MOQ):	5
NSN:	5305-01-603-8744
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1581C4T12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.403 Inches Nominal
Fastener Length:	1.138 Inches Minimum And 1.168 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.3504 Inches Minimum And 0.3988 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.74 Inches Minimum And 0.76 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	3700 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt,shear,100 Deg Flush Reduced Head,offset Cruciform,offset Cruciform-ribbed & Dt Slot,95 Ksi Fsu
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Cres 286 Conform To Ams5731,ams5732,ams5737 Or Ams5853 National Std/spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Passivate law Ams2700 Method 1,type 2 Or 8,class 1 National Std/spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1581C4T12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.