

Description

Fastener Length: 57/64", Thread: 1/4-24, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1581C5T6 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-044-4415 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1581C5T6 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.476 Inches Minimum And 0.526 Inches Maximum |
| Fastener Length: | 0.861 Inches Minimum And 0.891 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.429 Inches Minimum And 0.479 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1581 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581C5T6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.