

**Description**

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1581F3R12
Minimum Qty (MOQ):	10
NSN:	5305-01-193-4513
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1581F3R12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.338 Inches Minimum And 0.388 Inches Maximum
<b>Fastener Length:</b>	1.098 Inches Minimum And 1.128 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.2578 Inches Minimum And 0.3047 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
<b>Surface Treatment:</b>	Chromate Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1581 Professional/industrial Association Standard

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1581F3R12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.