

Description

length: 0.863", thread: 10-32 shear 100°, flush reduced head bolt - alloy steel offset cruciform

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581F3T8
Minimum Qty (MOQ):	100
NSN:	5305-01-477-2865
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1581F3T8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	0.848 Inches Minimum And 0.878 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.2578 Inches Minimum And 0.3047 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	F16
Nominal Thread Diameter:	0.188 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1581F3T8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.