



Military-Fasteners.com

P/N NAS1581F3T8X

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581F3T8X
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-399-3097
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1581F3T8X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	0.848 Inches Minimum And 0.878 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.2578 Inches Minimum And 0.3047 Inches Maximum
Shoulder Diameter:	0.2041 Inches Minimum First Shoulder And 0.2051 Inches Maximum First Shoulder
Shoulder Length:	0.490 Inches Minimum First Shoulder And 0.510 Inches Maximum First Shoulder
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1581 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F3T8X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.