

Description

length: 0.528", thread: 1/4-28 shear 100°, flush reduced head bolt - alloy steel offset cruciform

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1581F4T2
Minimum Qty (MOQ):	50
NSN:	5305-01-448-5088
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1581F4T2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Nominal
Fastener Length:	0.513 Inches Minimum And 0.543 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.350 Inches Minimum And 0.399 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1581 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1581F4T2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.