

**Description**

Fastener Length: 1-31/32", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1581F4T25
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-425-8826
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS1581F4T25 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.403 Inches Nominal
<b>Fastener Length:</b>	1.950 Inches Minimum And 1.980 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.3504 Inches Minimum And 0.3988 Inches Maximum
<b>Grip Diameter:</b>	0.248 Inches Nominal
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.965 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	3200 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6047 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty 2, Cl 2 Fed Spec 1st Treatment Response Overall Or Qq-p-35 Fed Spec 2nd Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1581 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F4T25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.