

P/N NAS1581F5R21

Description

Fastener Length: 1-53/64", Thread: 1/4-24, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1581F5R21

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-228-0561

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1581F5R21 Specifications

Thread Class: Right-hand Chread Length: O.476 Inches Minimum And 0.526 Inches Maximum Fastener Length: 1.798 Inches Minimum And 1.828 Inches Maximum Head Style: Flat Countersunk Head Diameter: O.429 Inches Minimum And 0.479 Inches Maximum O.3110 Inches Minimum And 0.3120 Inches Maximum
Thread Length: 0.476 Inches Minimum And 0.526 Inches Maximum 1.798 Inches Minimum And 1.828 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.429 Inches Minimum And 0.479 Inches Maximum
Fastener Length: 1.798 Inches Minimum And 1.828 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.429 Inches Minimum And 0.479 Inches Maximum
Head Style: Flat Countersunk Head Diameter: 0.429 Inches Minimum And 0.479 Inches Maximum
Head Diameter: 0.429 Inches Minimum And 0.479 Inches Maximum
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style: Offset Cruciform (torque Set)
Nominal Thread Diameter: 0.312 Inches
Grip Length: 1.302 Inches Minimum And 1.322 Inches Maximum
Thread Quantity Per Inch: 24
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Hardness Rating: 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish: 32.0 Microinches Grip
Surface Finish: 32.0 Microinches Threads
Special Features: Internal Drive Ribbed
Material: Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740 Overall
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment: Cadmium And Chromate Overall
Surface Treatment Document And Classification: Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf
Specification/standard Data: 80205-nas1581 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F5R21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F5R21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F5R21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F5R21 and selecting the quantity you want of the property of the p