



Military-Fasteners.com

P/N NAS1581F5T18

Description

Fastener Length: 1-41/64", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1581F5T18 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-318-5301 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1581F5T18 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.491 Inches Minimum And 0.511 Inches Maximum |
| Fastener Length: | 1.611 Inches Minimum And 1.641 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.429 Inches Minimum And 0.479 Inches Maximum |
| Head Height: | 0.070 Inches Nominal |
| Grip Diameter: | 0.311 Inches Minimum And 0.312 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.115 Inches Minimum And 1.135 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty li,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1581 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F5T18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.