

## Description

Fastener Length: 1-39/64", Thread: 3/8-24, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1581F6T16
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-390-6460
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

# P/N NAS1581F6T16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Nominal
Fastener Length:	1.579 Inches Minimum And 1.609 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.515 Inches Minimum And 0.566 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1581 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F6T16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.