

Description

Fastener Length: 1-1/8", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1581F6T9 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-443-7543 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS1581F6T9 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Nominal |
| Fastener Length: | 1.156 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.5149 Inches Nominal |
| Head Height: | 0.081 Inches Nominal |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.562 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 16000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| iii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Material: | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1581F6T9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.